



## IKARIA

Material	steel pipes $\varnothing$ 28 mm / steel pipes $\varnothing$ 22 mm
Connection thread	4 x G1/2"
Testing overpressure	1,3 MPa
Max. operating overpressure	1,0 MPa
Max. operating temperature	110 °C
Number of pipes	14, 24, 36



IKARIA 1212 x 600

Type H/L [mm]	Depth B [mm]	Weight [kg]	Water capacity [l]	Temperature exponent [n]	Heating Output [W]			Recommended power input paint [W]	Recommended power input chrome [W]	Connection span [mm]
					75/65/20 °C	70/55/20 °C	55/45/20 °C			
732/500	48	6,1	2,7	1,187	337	278	184	300	200	464
732/600	48	7,0	3,2	1,187	389	321	212	400	300	564
1212/500	48	10,3	4,7	1,187	573	472	312	600	400	464
1212/600	48	11,8	5,4	1,187	663	547	362	700	500	564
1772/500	48	15,4	7,0	1,187	855	705	466	800	600	464
1772/600	48	17,7	8,1	1,187	989	815	539	1000	700	564

Thermal power measuring follows in accordance with EN 442.  
 Chrome surface treatment reduces heating capacity by ~30 %.  
 Accessories (page 64, 65 and 66) is not part of the radiator.

