

MAPIA LIGHT



MAPIA LIGHT


Material	steel profiles D35 × 41 mm / steel profiles 50 × 10 mm
Connection thread	4 × G1/2"
Testing overpressure	0,65 MPa
Max. operating overpressure	0,5 MPa
Max. operating temperature	110 °C
Number of profiles	10, 16, 24








MAPIA LIGHT 1180 × 600

Type H/L [mm]	Depth B [mm]	Weight [kg]	Water capacity [l]	Temperature exponent [n]	Heating Output [W]			Recommended power input paint [W]	Recommended power input chrome [W]	Connection span [mm]
					75/65/20 °C	70/55/20 °C	55/45/20 °C			
725/500	35	7,6	3,0	1,273	358	291	187	400	-	459
725/600	35	8,8	3,3	1,273	421	342	220	400	-	559
1180/500	35	12,1	4,8	1,270	558	454	292	600	-	459
1180/600	35	14,2	5,3	1,270	658	535	344	700	-	559
1765/500	35	18,2	7,2	1,267	821	668	430	800	-	459
1765/600	35	21,2	8,0	1,267	966	786	506	1000	-	559

Thermal power measuring follows in accordance with EN 442.
Accessories (page 64, 65 and 66) is not part of the radiator.



Connection options



DMAL 0725 0500...
DMAL 0725 0600...

DMAL 1180 0500...
DMAL 1180 0600...

DMAL 1765 0500...
DMAL 1765 0600...