

SPIRA RADIUS



SPIRA RADIUS

Material	steel pipes \varnothing 22 mm / steel profiles D1/2 52 x 37 mm
Connection thread	4 x G1/2"
Testing overpressure	0,65 MPa
Max. operating overpressure	0,5 MPa
Max. operating temperature	110 °C
Number of pipes	14, 22, 33



SPIRA RADIUS 1180 x 600

Type H/L [mm]	Depth B [mm]	Weight [kg]	Water capacity [l]	Temperature exponent [n]	Heating Output [W]			Recommended power input		Connection span [mm]
					75/65/20 °C	70/55/20 °C	55/45/20 °C	paint [W]	chrome [W]	
730/500	78	6,6	4,5	1,263	316	257	166	300	200	443
730/600	102	7,5	5,0	1,263	370	302	194	400	300	546
1180/500	78	10,4	7,3	1,272	492	400	257	500	300	443
1180/600	102	11,8	8,0	1,272	576	468	301	600	400	546
1765/500	78	15,6	10,9	1,259	741	604	390	700	500	443
1765/600	102	17,7	12,0	1,259	869	708	457	900	600	546

Thermal power measuring follows in accordance with EN 442.
 Chrome surface treatment reduces heating capacity by ~30 %.
 Accessories (page 64, 65 and 66) is not part of the radiator.

POSSIBILITY OF THE MIDDLE CONNECTION (per order)

radius middle connection standard

radius middle connection with cover

Connection options

DSPR 0730 0500...
DSPR 0730 0600...

DSPR 1180 0500...
DSPR 1180 0600...

DSPR 1765 0500...
DSPR 1765 0600...

	Length [mm]	A [mm]	X [mm]
Plastic brackets (RAL 9006, 9016)	500	113-122	62-72
	600	112-122	39-49
Metal brackets (Other colours)	500	107-117	56-66
	600	112-122	39-49