

| Contact details | ISAN Radiátory s.r.o., Poříčí 26, 678 01 Blansko CZ | | | | | |
|---|---|-------|------|--|------|--|
| Model identifier(s): DxxxxxxxxxxFKxxx | | | | | | |
| Item | Symbol | Value | Unit | Item | Unit | |
| Heat output | | | | Type of heat output / room temperature control (select one) | | |
| Nominal heat output | P_{nom} | 0,400 | kW | single stage heat output and no room temperature control | no | |
| Minimum heat output (indicative) | P_{min} | N.A. | kW | two or more manual stages, no room temperature control | no | |
| Maximum continuous heat output | $P_{max,c}$ | 0,400 | kW | with mechanic thermostat room temperature control | no | |
| Power consumption | | | | with electronic room temperature control | no | |
| In off mode | P_o | N.A. | W | electronic room temperature control plus day timer | no | |
| In standby mode | P_{sm} | 0,72 | W | electronic room temperature control plus week timer | yes | |
| In idle mode | P_{idle} | 0,72 | W | Other control options (multiple selections possible) | | |
| In network standby | P_{nsm} | N.A. | W | room temperature control, with presence detection | no | |
| Standby mode with display of information or status | | | yes | room temperature control, with open window detection | yes | |
| Seasonal space heating energy efficiency in active mode | $\eta_{s,on}$ | 96,00 | % | distance control option | no | |
| | | | | adaptive start control | no | |
| | | | | working time limitation | yes | |
| | | | | black bulb sensor | no | |
| | | | | self-learning functionality | no | |
| | | | | control accuracy | yes | |

| Contact details | ISAN Radiátory s.r.o., Poříčí 26, 678 01 Blansko CZ | | | | | |
|---|---|-------|------|--|------|--|
| Model identifier(s): DxxxxxxxxxxFKxxx | | | | | | |
| Item | Symbol | Value | Unit | Item | Unit | |
| Heat output | | | | Type of heat output / room temperature control (select one) | | |
| Nominal heat output | P_{nom} | 0,600 | kW | single stage heat output and no room temperature control | no | |
| Minimum heat output (indicative) | P_{min} | N.A. | kW | two or more manual stages, no room temperature control | no | |
| Maximum continuous heat output | $P_{max,c}$ | 0,600 | kW | with mechanic thermostat room temperature control | no | |
| Power consumption | | | | with electronic room temperature control | no | |
| In off mode | P_o | N.A. | W | electronic room temperature control plus day timer | no | |
| In standby mode | P_{sm} | 0,72 | W | electronic room temperature control plus week timer | yes | |
| In idle mode | P_{idle} | 0,72 | W | Other control options (multiple selections possible) | | |
| In network standby | P_{nsm} | N.A. | W | room temperature control, with presence detection | no | |
| Standby mode with display of information or status | | | yes | room temperature control, with open window detection | yes | |
| Seasonal space heating energy efficiency in active mode | $\eta_{s,on}$ | 96,00 | % | distance control option | no | |
| | | | | adaptive start control | no | |
| | | | | working time limitation | yes | |
| | | | | black bulb sensor | no | |
| | | | | self-learning functionality | no | |
| | | | | control accuracy | yes | |

| Contact details | ISAN Radiátory s.r.o., Poříčí 26, 678 01 Blansko CZ | | | | | |
|---|---|-------|------|--|------|--|
| Model identifier(s): DxxxxxxxxxxFKxxx | | | | | | |
| Item | Symbol | Value | Unit | Item | Unit | |
| Heat output | | | | Type of heat output / room temperature control (select one) | | |
| Nominal heat output | P_{nom} | 0,800 | kW | single stage heat output and no room temperature control | no | |
| Minimum heat output (indicative) | P_{min} | N.A. | kW | two or more manual stages, no room temperature control | no | |
| Maximum continuous heat output | $P_{max,c}$ | 0,800 | kW | with mechanic thermostat room temperature control | no | |
| Power consumption | | | | with electronic room temperature control | no | |
| In off mode | P_o | N.A. | W | electronic room temperature control plus day timer | no | |
| In standby mode | P_{sm} | 0,72 | W | electronic room temperature control plus week timer | yes | |
| In idle mode | P_{idle} | 0,72 | W | Other control options (multiple selections possible) | | |
| In network standby | P_{nsm} | N.A. | W | room temperature control, with presence detection | no | |
| Standby mode with display of information or status | | | yes | room temperature control, with open window detection | yes | |
| Seasonal space heating energy efficiency in active mode | $\eta_{s,on}$ | 96,00 | % | distance control option | no | |
| | | | | adaptive start control | no | |
| | | | | working time limitation | yes | |
| | | | | black bulb sensor | no | |
| | | | | self-learning functionality | no | |
| | | | | control accuracy | yes | |

| Contact details | ISAN Radiátory s.r.o., Poříčí 26, 678 01 Blansko CZ | | | | | |
|---|---|-------|------|--|------|--|
| Model identifier(s): DxxxxxxxxxxFKxxx | | | | | | |
| Item | Symbol | Value | Unit | Item | Unit | |
| Heat output | | | | Type of heat output / room temperature control (select one) | | |
| Nominal heat output | P_{nom} | 1,000 | kW | single stage heat output and no room temperature control | no | |
| Minimum heat output (indicative) | P_{min} | N.A. | kW | two or more manual stages, no room temperature control | no | |
| Maximum continuous heat output | $P_{max,c}$ | 1,000 | kW | with mechanic thermostat room temperature control | no | |
| Power consumption | | | | with electronic room temperature control | no | |
| In off mode | P_o | N.A. | W | electronic room temperature control plus day timer | no | |
| In standby mode | P_{sm} | 0,72 | W | electronic room temperature control plus week timer | yes | |
| In idle mode | P_{idle} | 0,72 | W | Other control options (multiple selections possible) | | |
| In network standby | P_{nsm} | N.A. | W | room temperature control, with presence detection | no | |
| Standby mode with display of information or status | | | yes | room temperature control, with open window detection | yes | |
| Seasonal space heating energy efficiency in active mode | $\eta_{s,on}$ | 96,00 | % | distance control option | no | |
| | | | | adaptive start control | no | |
| | | | | working time limitation | yes | |
| | | | | black bulb sensor | no | |
| | | | | self-learning functionality | no | |
| | | | | control accuracy | yes | |

| Contact details | ISAN Radiátory s.r.o., Poříčí 26, 678 01 Blansko CZ | | | | | |
|---|---|-------|------|--|------|--|
| Model identifier(s): DxxxxxxxxxxFKxxx | | | | | | |
| Item | Symbol | Value | Unit | Item | Unit | |
| Heat output | | | | Type of heat output / room temperature control (select one) | | |
| Nominal heat output | P_{nom} | 1,200 | kW | single stage heat output and no room temperature control | no | |
| Minimum heat output (indicative) | P_{min} | N.A. | kW | two or more manual stages, no room temperature control | no | |
| Maximum continuous heat output | $P_{max,c}$ | 1,200 | kW | with mechanic thermostat room temperature control | no | |
| Power consumption | | | | with electronic room temperature control | no | |
| In off mode | P_o | N.A. | W | electronic room temperature control plus day timer | no | |
| In standby mode | P_{sm} | 0,72 | W | electronic room temperature control plus week timer | yes | |
| In idle mode | P_{idle} | 0,72 | W | Other control options (multiple selections possible) | | |
| In network standby | P_{nsm} | N.A. | W | room temperature control, with presence detection | no | |
| Standby mode with display of information or status | | | yes | room temperature control, with open window detection | yes | |
| Seasonal space heating energy efficiency in active mode | $\eta_{s,on}$ | 96,00 | % | distance control option | no | |
| | | | | adaptive start control | no | |
| | | | | working time limitation | yes | |
| | | | | black bulb sensor | no | |
| | | | | self-learning functionality | no | |
| | | | | control accuracy | yes | |