Design Radiators by ISAN

Atria

The width of the horizontal profiles lends Atria units a clear, original appearance. Each radiator will become a striking design feature, especially in colour variations with a structured surface such as lava ash, cinnamon or sapphire.

bath accessories → 145
connection sets → 146
electric regulators → 154
colour ref. chart → 159

Atria

Code Height (H) /Length (L) [mm]	Depth (B) [mm]	Weight [kg]	Water capacity [l]	Temperature exponent [-]	Output 75/65/20°C [W]	Power input [W]	Connection span [mm]	White colour RAL 9016	Electric
DLAV 0800 0550	**41**	**10,7**	**3,4**	**1,220**	**408**	**400**	**512**	✓	✓
DLAV 1120 0550	**41**	**14,8**	**4,8**	**1,238**	**569**	**600**	**512**	✓	✓
DLAV 1520 0550	**41**	**21,1**	**6,8**	**1,230**	**761**	**800**	**512**	✓	✓

For ordering procedure see page 160 / The weight of radiators does not include water and packaging.

Technical information

Material	steel profiles 30×30 mm
	steel profiles horizontally 70×11 mm
Connection threads	4×G1/2"
Testing overpressure	0,65 MPa
Max. operating overpressure	0,5 MPa
Max. operating temperature	110 °C
Number of profiles	8, 11, 16

Modification options

Surface treatment	colour
Height range [mm]	640-2000 (increase of 80)
Length range [mm]	420-1000 (increase of 10)
Change of dimensions	additional charge
Electric version	YES (additional charge)
Standard connection (SK)	STANDARD
Middle connection (SM)	YES (additional charge)
Side connection (SB)	NO
One-sided into space fixing	NO

Type height (H) / length (L) [mm]

H 0800 L 0550 | H 1120 L 0550 | H 1520 L 0550

Mounting



Type	X [mm]	A [mm]
Metal brackets	55-65	81-91

Connection options

The type of connection must be specified in the order; for more information see page 160, positions 13 and 14.

Magnetic hooks